

Clean Mesh™ 5" Gutter Guard Installation Instructions

Tools: Ladder, Safety Glasses, Gloves, Measuring Tape, Pencil, Tin Snips & Metal Bending Tool

Before beginning the **Clean Mesh™** installation, the gutters should be **cleaned and tested** to ensure they are free of clogs, draining correctly, and in proper working order.

Step 1. Place the **Clean Mesh™** panel onto the top of the gutter, the panel should be approximately $\frac{1}{4}$ " larger than the gutter opening. Press the rear section downward to meet the fascia or drip edge, this pressure fit will hold the panel in place. Secure to the gutter lip using min. #6 x $\frac{1}{2}$ " piercing point screws approx. 1" from each end and in the middle of the panel. Butt additional panel ends tight together before securing in place.



Step 2. At the gutter corner, begin the **Clean Mesh™** panel angle cut at the front lip, then snip the weep hole leg. Cut and remove the face of the next **Clean Mesh™** panel to conform to the angle and butt tight together.



Step 3. At the termination end of the gutter system, you will need to snip and remove the panel nose and the weep hole leg approximately 2 inches from the gutter end. Bend the 2" section downward at a 90° angle to create a cap at the end of the system.



Step 4. Optional screws may be utilized at the sight line channel into the fascia to provide additional structural support for the entire gutter system.



- Always be aware of power line wires!
- Move your ladder into position for each panel installation.
- Always use a dissimilar metal barrier when installing panels in contact with different metals.
- Fascia mounts are ideal for metal and tile roofing, or screen room installations.
- Always maintain a positive panel slope, with no reverse slope.